

**All motors**

Permanent Magnets AC,
high efficiency, IP65

Intermittent kW: S3 10% - 10'
(1 minute at intermittent
power then reduced for 9
minutes to return to stable
temperature)

Ratings

Cruising speed: 70% of rated
motor rpm

Medium Duty: liquid cooled
motor, up to 1000 hours/
year, intermittent kW allowed

Heavy Duty: liquid cooled
motor, up to 3000 hours
per year, intermittent kW
allowed, max 80% of time at
rated rpm and load

Ratings

For Torque calculation use
the formula:

$$T \text{ (Nm)} = \frac{\text{kW}}{\text{rpm}} \times 9550$$

Batteries can be of any chemistry and brand.

TF BATTERY	min [Vdc]	max [Vdc]
51	44	59
102	88	118
140	121	162
307	264	355
409	352	473

To evaluate the battery characteristics in case of customer's
supply please use the following formula giving the max (A)
current required by Transfluid's motors:

$$I \text{ (A)} = \frac{\text{kW} \times 1000}{V} \times 2$$

DriveMaster - Liquid cooled system specifications

Product code	Model	Motor Size	Nominal kW	Intermittent kW	Battery Vdc	Motor rpm
BV101608W	DriveMaster 3W	180-4	2.5	3	48 (51)	1500
BV100854W	DriveMaster 7W	180-8	5	7	48 (51)	1500
BV100808W	DriveMaster 10W	180-12	8	10	48 (51)	1500
BV100810W	DriveMaster 15W	220-20	10	15	48 (51)	1500
BV101610W	DriveMaster 20W EVO	220-20 (s)	15	20	48 (51)	1500
BV100812W	DriveMaster 20W	220-20	15	20	96 (102)	1500
BV101288W	DriveMaster 30W	220-35	25	30	144 (140)	1500
BV101642W	DriveMaster 45W	300-50	35	45	144 (140)	1500
BV101580W	DriveMaster 55W	300-75	45	55	144 (140)	1500

(s) Special
() Transfluid battery

Unit 4 Flightway Dunkeswell
Honiton Devon EX14 4RD

T +44(0) 1404 892 940
E info@lynchmotors.co.uk

LYNCHMOTORS.CO.UK

**2 YEAR EXTENDABLE WARRANTY
WITH ALL OF OUR MOTORS**